

237-2% AF Neo-Asphalt (brush grade)**DESCRIPTION:**

Karnak #237-2%AF Neo-Asphalt is an asbestos-free cold applied, rubberized asphalt cement, designed especially as an adhesive for paving blocks and pressed asphalt bricks, eliminating the need for a hot kettle.

PHYSICAL PROPERTIES:

| | |
|--|--------------------------------|
| Viscosity @ 25C: 12,000-18,000 C.P.S. | Softening Point of Base: 200°F |
| Specific Gravity @ 25C: 1.02 | Penetration of Base: 24 |
| Weight per Gallon @ 25C: 8.1 lbs. | Ductility: 130 cm |
| % Solids by Weight: 70% | % Inorganic Material: 6.5% |
| % Solids by Volume: 64% | % Long Fiber 10% |
| Flash Point: 107°F | % Neoprene 2% min. |
| Softening Point of Rubber Blend: 150°F | |

SURFACE PREPARATION:

All surfaces should be clean, dry, free from oil, grease or other foreign matter.

APPLICATION:

Karnak #237-2%AF Neo-Asphalt can be applied to either concrete or macadam (blacktop) using a brush or squeegee. For best results, allow a minimum of 2-3 hours open air time or until material becomes tacky and just skins over prior to embedding the paving blocks.

NOTE:

Karnak #237-2%AF Neo-Asphalt should be thoroughly **mechanically mixed** prior to application. Macadam (blacktop) surfaces should be cured prior to applying Karnak #237-2%AF Neo-Asphalt.

COVERAGE:

Apply at the rate of .5 - 1 gallon per 30-50 sq. ft. Do not exceed coverage rate.

CARE OF TOOLS:

Tools and other equipment should be thoroughly cleaned with mineral spirits, taking necessary precautions when handling combustible materials.

CAUTION:

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not** induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin.** Dispose of in an environmentally safe manner.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066 732-388-0300
 • 800-526-4236 • FAX: 732-388-9422 WEB:
<http://www.karnakcorp.com>

Sealants, Caulking, Flooring

Read Material Safety Data Sheets before using this product.

237-2% AF Neo-Asphalt

(brush grade)

PACKAGING:

Available in 5 gallon pails and 55 gallon drums.

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Sealants, Caulking, Flooring

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066 732-388-0300

• 800-526-4236 • FAX: 732-388-9422 WEB:

<http://www.karnakcorp.com>

CH0105