

Metal Seam Sealing Tape

DESCRIPTION:

Karnak Metal Seam Sealing Tape is a butyl adhesive fabric for use on properly prepared metal roof surfaces. Its ease of application, durability and superior adhesion make Karnak Metal Seam Sealing Tape an excellent choice for metal roof applications.

USES:

Karnak Metal Seam Sealing Tape is designed for sealing horizontal and vertical seams on properly prepared metal roof surfaces. Its ease of use allows for quicker installations than traditional sealing materials. Coating applications can take place faster also speeding system installations.

ADVANTAGES:

1. Correct protective mil thickness every time. 2. Solvent-free.
3. Superior adhesive bond that remains flexible. 4. Forms a durable, weather resistant rubber bond. 5. No drying time required. 6. Save 50% in material and labor costs to seal seams.

SURFACE PREPARATION:

All surfaces to be sealed must be clean, dry and free from oil, grease, dirt, dust and other foreign matter.

APPLICATION:

After surfaces have been properly prepared, apply Karnak Metal Seam Sealing Tape to the roof surface exactly the first time. Trying to remove may damage seam sealing tape and roofing. Do not stretch. Press down firmly starting at the center and working towards the outside edge, removing bubbles. Slight wrinkling should not affect performance of seal. Edges must be free of fishmouths, uplifts and tunnels.

Finish seam by applying 502 Seam Sealer, 505 Seam Sealer or 229AR-Elastomeric over the taped seam. Using a brush, apply seam sealer at a 1/16" thickness to completely cover seam sealing tape and feather out 2". Allow to cure for 24 hours.

Meal Seam Sealing Tape

PHYSICAL PROPERTIES:

Appearance:	Grayish fabric with gray sealant
Low Temperature Flex.:	Pass, No Cracking
Bonding Time:	Immediate, Full bond within 24 hours
Tensile Strength:	147 psi
Peel Strength:	10 lbs. per linear inch
Application Temp.:	35°F to 110°F
Operating Limits:	-20°F to 200°F

CAUTION:

Surfaces must be clean, free of moisture and contaminants. Do not stretch during application. On exposed areas, must coat with elastomeric coating or equivalent. Do not leave exposed. See manufacturer's safety data sheet. **KEEP AWAY FROM CHILDREN.** For industrial, professional use only.

COLD-PROCESS SYSTEMS AND COATINGS, EITHER EMULSION OR SOLVENT BASED, SHOULD ONLY BE INSTALLED ON DECKS WITH POSITIVE DRAINAGE. PER NRCA, (NATIONAL ROOFING CONTRACTORS ASSOCIATION) "THE CRITERIA FOR JUDGING PROPER SLOPE FOR DRAINAGE IS THAT THERE BE NO EVIDENCE OF STANDING WATER ON THE DECK 48 HOURS AFTER IT STOPS RAINING."

PACKAGING:

Available in rolls:
4" x 50' (12 rolls per box)

If further information is needed, contact Karnak Technical Services at 1-800-526-4236.

Metal
Roofing