

15 Smooth MUCK®

DESCRIPTION:

Smooth MUCK® asphalt flashing cement is composed of selected crude asphalts, asbestos-free fibers and refined solvents that dries to a tough waterproof coating. Use to seal leaks on asphalt roofs, concrete and metal roofs, shingles, gutters, downspouts, around chimneys, flues and skylights as well as for general purpose use in the maintenance of all exposed building and structures. Available in three consistencies: Summer, Semi and Winter.

PRODUCT FEATURES:

- Smooth trowel grade consistency
- Tough waterproof film
- Won't run or sag on vertical surfaces

USES:

Smooth MUCK® is a general purpose flashing cement for repairing and sealing leaks on asphalt roofs, concrete and metal roofs, shingles, gutters, downspouts, around chimneys, flues and skylights as well as for general purpose use in the maintenance of all exposed building and structures.

SURFACE PREPARATION:

All surfaces to be sealed must be clean, dry and free from oil or grease, dirt, dust and other foreign matter.

APPLICATION:

Trowel Smooth MUCK® to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks. To repair large cracks, breaks and blisters, embed either asphalt cotton or fiberglass membrane between two application of Smooth MUCK® over the damaged area.

PRODUCT SPECIFICATIONS:

ASTM D-4586, Type I, Class I

Federal Specification SS-C-153 Type I (Non-Asbestos)

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>



15 Smooth MUCK®

CAUTION:

Do not use near heat or open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner. Avoid getting in eyes. Use only with adequate ventilation. Cover air intakes during application and while drying.

PACKAGING:

Available in 5 gallon pails.

If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

