

# 18 Perfectseal Flashing Cement (Asbestos-Free)

**DESCRIPTION:**

KARNAK 18 Perfectseal Flashing Cement is a scientifically compounded composition of selected asphalts, mineral fibers, and refined solvents that are product when applied dries to a tough, flexible, water-resistant and manufactured to a heavy consistency. Designed for application by trowel 18 is a durable cement with excellent adhesion and weathering characteristics. This corrosion proof coating that provides excellent performance over a wide range of temperature and weather conditions. Available in three consistencies: Summer, Semi and Winter.

**USES:**

KARNAK 18 Perfectseal Flashing Cement is a general purpose cement for repair- ing leaks in shingles, concrete, metal or asphalt roofs, flashings on walls, chimneys, flues, down- spouts and cornices. Excellent for sealing cracks in concrete, brick, as a joint filler for pre-cast roof slabs and general purpose use in maintenance of exposed buildings and structures.

**SURFACE PREPARATION:**

All surfaces should be clean, dry and free from oil or grease, dust, dirt, loose paint or other foreign matter prior to application.

**APPLICATION:**

Spread KARNAK 18 Perfectseal Flashing Cement to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks. To repair large cracks, breaks and blisters, spread KARNAK 18 Perfectseal Roof Cement over the damaged area, then embed KARNAK Cotton, Glass or Poly-Mat Membrane reinforcement and then apply another coat of KARNAK 18 Perfectseal Roof Cement over the entire patch.

**PRODUCT SPECIFICATIONS:**

ASTM D-4586, Type I Class I

Fed. Spec. SS-C-153 Type 1 (except non-Asbestos)

**KARNAK**

Revised 09.10.18

CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>



# 18 Perfectseal Flashing Cement (Asbestos-Free)

**PHYSICAL PROPERTIES:**

1. Consistency: A smooth, heavy trowel consistency which will readily spread on and adhere to surfaces without sagging.
2. Character of Dried Film: Uniform, excellent adhesion to masonry, steel, cured concrete, shingles, asphalt roofing and a variety of other surfaces.
3. Has excellent resistance to flow at high temperatures when used on a vertical surface.

**CAUTION:**

Do not use near heat or open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Avoid getting in eyes. Use only with adequate ventilation. Cover air intakes during application and while drying.

**PACKAGING:**

Available in 5 gallon pails and 3 gallon buckets.

**If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.**

**KARNAK**

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>

