

105 Tac-Kote

DESCRIPTION:

KARNAK 105 Tac-Kote is a cold applied asphalt cut-back designed specifically as a primer/adhesive for use under asphalt based roadways.

FEATURES, BENEFITS AND ADVANTAGES:

105 Tac-Kote penetrates capillaries to bind and seal dusty surfaces to provide the correct base for subsequent toppings.

SURFACE PREPARATION:

Surfaces to be treated with 105 Tac-Kote should be oil and moisture free in order to assure proper penetration. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals.

APPLICATION:

105 Tac-Kote is easily applied by brush, squeegee or spray. Apply at the rate of 1 to 1.5 gallons per 100 sq. ft. Actual rate may vary due to the nature of the substrate.

COVERAGE:

Apply at the rate of 1 to 1.5 gallons per 100 sq. ft.

SPECIFICATIONS:

ASTM D-2028 RC-250

AASHTO M-81

CAUTION:

Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not** induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin.** Dispose of in an environmentally safe manner.

PACKAGING:

Available in 5 gallon pails and 55 gallon drums.

If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.

CLARK
, NJ
07066
732-
388-
0300 •
800-
526-
4236 •
FAX:
732-
388-
9422
WEB:
[http://
www.k
arnakc
orp.co
m](http://www.karnakcorp.com)

KARNAK