

## 507 SPC Primer/Wash (For EPDM Membranes)

**DESCRIPTION:**

KARNAK 507 SPC Primer / Wash is a water-based cleaner designed to safely clean and prepare EPDM roof surfaces for subsequent coatings and repairs.

**USES:**

507 SPC Primer / Wash is appropriate for use on new and weathered EPDM roof membranes.

**SURFACE PREPARATION:**

Surfaces should be free of all roof debris and in a water-tight condition. Recommended application temperature is 40°F and rising.

**APPLICATION:**

Apply 507 SPC Primer / Wash via a sprayer (Hudson-type agricultural) to the entire roof at an application rate of 500 square feet per gallon (0.20 gal. / 100 sq. ft.). Use a 3-4 foot arc pattern. Allow 507 SPC Primer to stand for 10-15 minutes. Clean EPDM roof with a commercial power washer (between 2000-3500 psi). When cleaning the EPDM, it should be done slowly and close to the surface in order to remove mica and inorganic release agents. Start washing up the roof. Then, back down to completely remove all residues. Care should be taken to not damage the EPDM roof membrane. Use caution when walking on roof surfaces, as they may be extremely slick.

\*Rinse thoroughly with power washer. The rinse step may be done at a faster pace than the cleaning step. In the final rinse water should be clear with no soap bubbles present. The EPDM membrane will range from muddy brown to black after washing with the 507 SPC Primer / Wash. When the surface is dry, coating may begin.

\*Due to the rinse water possibly containing dirt, mold, mildew algae and diluted 507 SPC, do not allow rinse to flow into drains or sewers leading to open bodies of water (lakes, ponds, streams, etc.). Do not dispose of the neat 507 SPC product into drains, sewers or open bodies of water. Rinse water from downspouts could stain concrete parking lots and decks as it flows to municipal drains. Because of this, temporary hoses should be used to direct the rinse water.

**KARNAK**

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>

## 507 SPC Primer/Wash (For EPDM Membranes)

**COVERAGE RATE:**

0.20 gallon per 100 sq. ft. (500 sq. ft. per gallon).

**PHYSICAL PROPERTIES:**

Weight Per Gallon:	8.6 lbs.
Color:	Clear
pH:	Neutral

**CAUTION:**

Do not apply when rain is imminent. Protect from freezing. Store in a cool, dry place. Keep container covered when not in use. Do not thin. Keep out of reach of children. Avoid prolonged contact with skin and eyes. In case of eye contact, immediately flush with copious amounts of water for at least 15 minutes. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Dispose of in an environmentally safe manner. Read Material Safety Data Sheets before using this product.

**PACKAGING:**

5-gallon pails & 1-gallon cans

**If further information is required, please contact KARNAK Technical Services Department at 800-526-4236.**

# KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066

732-388-0300 • 800-526-4236 • FAX: 732-388-9422

WEB: <http://www.karnakcorp.com>