

## 560 KARNA-Bond (Self-Sealing Tapes)

### DESCRIPTION:

KARNAK 560 KARNA-Bond self-sealing tapes are composed of highly adhesive micro-sealant non-curing rubber with a built-in-primer. These tapes were developed to quickly seal surfaces and stop the intrusion of moisture. The Tri-layer TPO reinforced film tapes are self-protecting making them a true “One-Step” sealant product that’s available in White, Black or Silver. The Fleece only film readily accepts solvent or acrylic based coatings and paints. The Fleece tape is ideal for use with metal roofing or single-ply roof applications as a seam and detail waterproofing fabric that bonds firmly to the surface. Double-Sided tape is great for sealing between metal-to-metal surfaces and to bond between seams of single ply roof membranes. Also use in creating seals for abutting and fastening mechanical equipment. Offers a high degree of vibration dampening. May also be molded to shape for custom sealing. The highly adhesive bond of 560 KARNA-Bond stays flexible in a wide range of temperatures for service use in all climates. White, Black and Silver should not be coated over.

### FEATURES, BENEFITS AND ADVANTAGES:

- Seals and waterproofs
- UV Stable – Can be left exposed (White, Black or Silver only)
- Bonds to many different roof surfaces and substrates.
- Easy release backing.
- Wide service temperature performance range.
- Bonds to fully-adhered solvent and acrylic based coatings and paints.
- Self-Healing
- VOC Free
- Fleece Faced Karna-Bond may be coated.

### USES:

560 KARNA-Bond is designed for sealing seams, flashing curbs and making repairs on metal roof surfaces, single ply roofs and many other building and roof surfaces. Ideal for sealing ductwork, trailers, mobile homes, trucks, gutters and skylights. Also has excellent adhesion for sealing to EPDM, Hypalon, and most PVC and TPO roof surfaces as well as to concrete, gypsum boards, plastic, glass, wood, asphalt, Plexiglas and most other common building materials. Its ease of use allows for quick repair installations. 560 KARNA-Bond Double-Sided is designed for bonding and sealing metal structures as well as offering a degree of vibration dampening. Use to bond seams of single ply roof membranes and in creating seals for abutting and fastening mechanical equipment.

**Note: Not intended for Asphaltic Surfaces.**

# KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066

732-388-0300 • 800-526-4236 • FAX: 732-388-9422

WEB: <http://www.karnakcorp.com>

## 560 KARNA-Bond (Self-Sealing Tapes)

### **SURFACE PREPARATION:**

All surfaces to be sealed should be dry, smooth, clean and free from dirt, dust, oxidized carbon dust, loose paint or coatings, oil, grease, rust, or other foreign matter. Recommended application temperature is 32°F to 120°F. Clean single ply membrane surfaces with toluene, xylene, acetone or single ply manufacturer's primer or slice wash. Clean metal with similar solvent or TSP substitute and water. Follow instructions and MSDS safety precautions of primer, wash or solvent manufacturer carefully when using.

### **APPLICATION:**

After surface has been properly prepared, cut desired length of 560 KARNA-Bond. Remove silicone release liner and position over desired area. Apply the tape directly to the area exactly the first time. Trying to remove may damage the tape and roofing surface. Press down firmly with a cloth pad, finger pressure or roller making sure tape stays conforming to the roof surface as you smooth out on to the surface. Edges should be free of fishmouths and tunnels. 560 KARNA-Bond Fleece should be coated over immediately. 560 KARNA-Bond Double-Sided is not meant to be exposed directly to the environment.

### **PHYSICAL PROPERTIES:**

Appearance:	Gray sealant (Double-Sided) or gray sealant with either a thin aluminum film (White, Black, Silver) or White Fleece
Thickness:	30 mils (+/- 2 mils) Double-Sided and Fleece only 20 mils (+/-2 mils) Silver, White, and Black only
Bonding Time:	Immediate, full bond within 24 hours
Peel Adhesion 90°:	17 lbs. ASTM D 1000
Application Temp:	32°F to 120°F
Service Temp:	-40°F to 210°F

### **CAUTION:**

Surfaces must be clean, free of moisture and contaminants. Keep out of reach of children. Read manufacturer's Material Safety Data Sheet before using. For professional use only.

# **KARNAK**

Revised 12.14.18

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>

## 560 KARNA-Bond (Self-Sealing Tapes)

### PACKAGING:

560 Fleece	2" x 50' rolls (12 per box)
	4" x 50' rolls (6 per box)
	6" x 50' rolls (4 per box)
	12" x 50' rolls (2 per box)
	24" x 50' rolls (1 per box)
560 White	4" x 50' rolls (6 per box)
	6" x 50' rolls (4 per box)
	12" x 50' rolls (2 per box)
	24" x 50' rolls (1 per box)
560 Black	4" x 50' rolls (6 per box)
	6" x 50' rolls (4 per box)
	12" x 50' rolls (2 per box)
	24" x 50' rolls (1 per box)
560 Silver	4" x 50' rolls (6 per box)
560 Double-Sided	1" x 50' rolls (24 per box)
	2" x 50' rolls (12 per box)
	4" x 50' rolls (12 per box)

**If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.**

# KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>