

112 Non-Fibered Asphalt Roof Coating

DESCRIPTION:

KARNAK 112 Non-Fibered Asphalt Roof Coating is a non-fibered asphalt coating designed for protecting a variety of roof surfaces. The finished coating forms a smooth, tough, flexible film that serves to help protect and extend the life of smooth surface BUR, APP and SBS modified bitumen membranes, metal roof surfaces and roll roofing.

FEATURES, BENEFITS AND ADVANTAGES:

1. Protects asphalt roofs from the hot sun and winter weather.
2. Forms a smooth, tough, elastic film.

USES:

112 Non-Fibered Asphalt Roof Coating can be applied on all types of smooth surface asphalt roofs including smooth BUR and APP modified bitumen membrane as well as SBS modified bitumen membrane, metal roof surfaces and roll roofing.

SURFACE PREPARATION:

All surfaces should be clean, dry and free from oil, grease, dust, dirt, loose paint or other foreign matter.

APPLICATION:

Apply with either a brush, roller or heavy-duty airless spray equipment in a smooth continuous coat over the entire roof area. Coating should be continuous and free of pinholes or holidays. If not, apply a second application at right angles to the original coat. Allow at least 24 hours drying time between coats. Do not apply to wet surfaces. .

COVERAGE:

Apply at the rate of 1 to 2 gallons per 100 sq. ft. Coverage rates may vary depending on the condition and porosity of the surface.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: www.karnakcorp.com

Revised 09.10.18



112 Non-Fibered Asphalt Roof Coating

PHYSICAL PROPERTIES:

Weight per Gallon:	7.80
Solids by Weight:	70%
Solids by Volume:	64%
Weight per Gallon:	7.8 lbs.
Color:	Black
Dry Time:	8 to 24 hours
Service Temp. Range:	-40°F to 180°F
VOC Content:	270 g/L maximum

CAUTION:

Do not use near open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

PACKAGING:

Available in 1 gallon cans, 5 gallon pails and 55 gallon drums.

If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: www.karnakcorp.com

