

155 Amphibikote (wet and dry)

DESCRIPTION:

KARNAK 155 Amphibikote is a carefully prepared, emergency roof cement with special water displacing characteristics, which ensures an effective bond to both wet and dry surfaces. The ability to adhere during inclement weather conditions makes 155 Amphibikote the first choice of both roofing contractors and plant engineers. 155 Amphibikote is composed of selected asphalts, mineral fillers combined with refined solvent, and special chemical ingredients which give it a unique water displacement quality. Available in three consistencies: Summer, Semi and Winter.

USES:

155 Amphibikote is a cold process, heavy bodied, trowel applied emergency roof cement ideal for repairing leaks in asphalt built-up roofs, flashing on walls, chimneys, skylights and vents, down-spouts and gutters. The dried film retains its flexibility and ductility so the coating will resist extreme variations in temperature and weather.

SURFACE PREPARATION:

Although it can be applied underwater for emergencies, it is best if all surfaces are clean, dry and free from oil, grease, dust, dirt, loose paint or foreign matter.

APPLICATION:

155 Amphibikote is ready to use directly from the container. No heating is required. Spread 155 Amphibikote by trowel to an average thickness of 1/8" (8 gals. per square per coat) or greater to all surfaces to be treated. To repair large cracks or breaks, spread 155 Amphibikote over the damaged area, then embed 34 Asphalt Cotton Fabric, 31 Fiberglass Membrane, 5540 Resat-Mat or 3036 Poly-Mat membrane Reinforcement and re-apply another coat of 155 Amphibikote over the entire patch.

SPECIFICATIONS:

ASTM D-4586 Type I Class I & Class II

ASTM D-3409

Federal Specification SS-C-153 Type I (except asbestos free)

KARNAK

Rev. 09.10.18

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>



155 Amphibikote (wet and dry)

CAUTION:

Do not use near open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

PACKAGING:

Available in 1 gallon cans, 3 gallon buckets, 5 gallon pails and 10.1oz cartridges.

If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.

KARNAK

Rev. 09.10.18

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

