

160.1 Amphibicaulk (wet and dry)

DESCRIPTION:

KARNAK 160.1 Amphibicaulk is a carefully prepared caulking-grade roof cement with special water displacing characteristics, which ensures an effective bond to both wet and dry surfaces. The ability to adhere during inclement weather conditions makes 160.1 Amphibicaulk the first choice of both roofing contractors and plant engineers. 160.1 Amphibicaulk is composed of selected asphalt, mineral fillers combined with refined solvent, and special chemical ingredients, which give it a unique water displacement quality.

USES:

160.1 Amphibicaulk is a cold process, heavy bodied, caulk-grade roof cement ideal for sealing leaks in and around asphalt built-up roofs, joints, chimney cracks, skylights, vents, down-spouts and gutters. The dried film retains its flexibility and ductility, so the caulking will resist extreme variations in temperature and weather. 160.1 Amphibicaulk may also be used to improve wind resistance on low slope shingle roofs.

SURFACE PREPARATION:

All surfaces should be clean and free from oil, grease, rust, dirt, and other foreign matter. Excess water should be removed, if possible, before application of 160.1 Amphibicaulk.

APPLICATION:

160.1 Amphibicaulk is ready to use directly from the container. No heating is required. Apply 160.1 Amphibicaulk directly over the cracks with a caulking gun.

SPECIFICATIONS:

ASTM D-4586 Type I Class I & Class II

ASTM D-3409

Federal Specification SS-C-153 Type I (except Non-Asbestos)

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

160.1 Amphibicaulk (wet and dry)

CAUTION:

Do not use near open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not** induce vomiting. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin.** Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

PACKAGING:

Available in 10.1 oz. caulking cartridges.

If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.

KARNAK

Rev. 09.10.18

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>