

# 170 Tar Cement

**DESCRIPTION:**

KARNAK 170 Tar Cement is a non-asbestos, tar base, plastic cement with unique water repellent characteristics. 170 Tar Cement is ideal for emergency roof repairs when roof leaks occur since it can actually be applied under water. Prepared to a heavy consistency for application by trowel to provide a durable, elastic coating with long-lasting, weather-resisting protection, this product gives excellent performance over a wide range of temperatures and conditions and has excellent self-healing properties.

**USES:**

A general purpose tar roof cement for repairing splits, cracks, holes and blisters on built up coal tar roofs. Average coverage is 1/16" thick or approximately 4 gallons per square.

**SURFACE PREPARATION:**

All surfaces should be clean, dry and free from oil or grease, dust, dirt, loose paint or other foreign matter.

**APPLICATION:**

Spread 170 Tar Cement to an average thickness of 1/16" to repair blisters, breaks or seams. This product is ready to use directly from the pail and should not be thinned in any way. In cold weather, stiffness can be reduced by storing the container in a warm area before using.

**SPECIFICATIONS:**

ASTM D-4022 (Except Asbestos-Free)  
Fed. Spec. SS-C-153 Type II.

**PHYSICAL PROPERTIES:**

Solids by Wt.:	77%
Solids by Volume:	66%
Wt. per Gallon:	9.59%

**RESISTANCE TO:**

Bacteria and corrosive acids of soil, chemical fumes and vapors, most acids and alkali occurring in industry.

**KARNAK**

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>

# 170 Tar Cement

**CAUTION:**

Do not use near open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

**PACKAGE SIZE:**

Available in 5 gallon pails.

**FOR THE PROTECTION OF FLAT- LEVEL TAR AND GRAVEL ROOFS:**

Product is self-healing and will run off any surface that is not level and flat.

Product has a strong odor. Cover air intakes while drying. Do not use around food products. Before starting work, protect exposed skin with ultra-violet blackout protective cream.

**FOR EXTERIOR USE ON FLAT SURFACES ONLY.**

**If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.**

**KARNAK**

Rev. 09.10.18

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>