

# 16 Double Coverage Cement

**DESCRIPTION:**

KARNAK 16 Double Coverage Cement is a bituminous based adhesive sealant designed for the application and repair of rolled roofing bituminous single-ply membranes. When properly utilized, this product adheres the membrane and seals the laps to prevent water intrusion.

**USES:**

1. Lap cement
2. Rolled roofing adhesive sealant
3. Blind nailing cement

**SURFACE PREPARATION:**

KARNAK 16 Double Coverage Cement is applied by brush, broom or squeegee. The area to be coated must be free and clean of all debris, dust and dirt. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals.

**COVERAGE:**

Under normal conditions, KARNAK 16 Double Coverage Cement should be applied at the rate of 2 to 3 gallons per 100 sq. ft.

**SPECIFICATIONS:**

ASTM D-3019 Type III

**CAUTION:**

Do not use near open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physician immediately. Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

**PACKAGING:**

Available in 5 gallon pails and 1 gallon pails.

If further information is needed, contact **KARNAK Technical Services at 1-800-526-4236**.

**KARNAK**

330 CENTRAL AVENUE, CLARK, NJ 07066  
732-388-0300 • 800-526-4236 • FAX: 732-388-9422  
WEB: <http://www.karnakcorp.com>

