

29 Perfectseal Quick-Grip Modified Bitumen Adhesive

DESCRIPTION:

KARNAK 29 Perfectseal Quick-Grip Modified Adhesive is a bituminous based adhesive sealant designed for the application and repair of modified bitumen single-ply membranes and bituminous single-ply membranes. When properly utilized this product adheres the membrane and seals the laps to prevent water intrusion. This economical and useful adhesive is designed to provide greater bonding strength.

USES:

Trowel Grade:

Designed as an adhesive sealant for SBS modified bitumen single-ply membranes and bituminous single-ply membranes. Use for flashing vertical surfaces, skylights, vents and pipes (Not for use around heated vents or pipes).

Brush Grade:

Designed as an adhesive sealant for SBS modified bitumen single-ply membranes and bituminous single-ply membranes such as conventional rolled roofing membranes and granular cap sheets.

APPLICATION:

Surface must be dry, clean and free of oil, grease, dust, dirt and all materials that might interfere with the adhesive bond. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals. Apply KARNAK 29 Perfectseal Quick-Grip Adhesive Brush Grade on **Horizontal** surfaces at a rate of approximately 1-2 gallons per 100 square feet; as determined by the irregularity and absorptive nature of the surface. Excessive use may create blistering. A rubber squeegee, brush or roller is the recommended application tool. Overlaps should be at least 4" wide. **Do not apply adhesive directly to decking or sheathing.** On **Vertical** surfaces apply KARNAK 29 Perfectseal Quick-Grip Trowel Grade at a 1/8" thickness, as determined by the irregularity and absorptive nature of the surface. Excessive use may create blistering. A 1/4" serrated trowel is the recommended application tool. Overlaps should be at least 4" wide. Application of one or multiple layer(s), allow a minimum of 15-20 minutes open air time before applying Cap Sheet or before each layer. Do not exceed 2 layers when installing with adhesive. Cover all air intakes during application and while drying. Application thickness, temperature, and number of membranes dictate how long it will take for the product to fully dry. Please consult membrane manufacturer for specific information and installation regarding their product.

CAUTION: Combustible Mixture. Do not use near fire or flame.
KEEP OUT OF REACH OF CHILDREN. Do not thin.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>



29 Perfectseal Quick-Grip Modified Bitumen Adhesive

WARNING: Keep away from open flame. Keep container closed when not in use. Avoid prolonged or repeated contact with skin or eyes. IF splashed in eyes, flush immediately with copious quantities of running water. Do not take internally. If swallowed, do not induce vomiting; call a physician immediately. Use with adequate ventilation. Provide adequate ventilation in confined areas during application. Vapors can cause headaches, nausea, dizziness and irritation of the respiratory tract, or unconsciousness. Wash exposed areas promptly and thoroughly after skin contact and before eating, drinking or using tobacco products. Prior to using this product it is necessary to read and understand the SDS which is available from your employer or by calling the KARNAK Technical Sales office at 1-800-526-4236. Dispose of in an environmentally safe manner. **Insure that proper ventilation is maintained during application and drying to prevent solvent fumes from entering the building.**

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

Revised 04.08.19

