

19 Ultra Rubberized Flashing Cement (wet/dry)

DESCRIPTION:

KARNAK 19 Ultra Flashing Cement is the next generation elastomeric flashing cement. Scientifically compounded with a selection of rubber reinforced asphalt, mineral fibers, and refined solvents. KARNAK 19 Ultra is manufactured to a heavy pliable consistency for ease of application by trowel. 19 Ultra provides a durable elastomeric coating of greater strength, excellent adhesion and high resistance to water and weathering.

KARNAK 19 Ultra is composed of special chemical ingredients which give it a unique water displacement quality (Wet/Dry). KARNAK 19 Ultra dries to a tough, flexible, waterproof and corrosion proof rubber coating which gives maximum protection and excellent performance over wide ranges of temperature and weather conditions. KARNAK 19 Ultra is available in 3 consistencies: Summer, Semi and Winter grade.

FEATURES, BENEFITS AND ADVANTAGES:

- Rubberized - elastomeric
- Wet or dry application
- Improved low-temperature flexibility
- Improved water and weather resistance
- Will not shrink or crack
- Smooth, easy to apply rubber-like trowel consistency
- Excellent adhesion
- Excellent resistance to flow (sag) at high roof temperatures
- Ready to apply - no mixing required
- Greater strength
- Cures faster than regular flashing cements
- VOC compliant
- ASTM compliant
- Sticks under water the first time.
- Can be used with fiberglass membrane under water.

USES:

KARNAK 19 Ultra Flashing Cement is a general purpose asbestos-free flashing cement for repairing leaks in shingles, concrete, metal or asphalt roofs, SBS and APP modified bitumen membranes flashings on walls, chimneys, flues, skylight flashings, downspouts and cornices.

KARNAK 19 Ultra is excellent for sealing cracks in concrete and brick, as a joint

KARNAK

Revised 11.08.19

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

MIAMI-DADE COUNTY
APPROVED

19 Ultra Rubberized Flashing Cement (wet/dry)

filler for precast roof slabs, for repair, patch and flashing detail on SBS and APP modified membranes, and for general purpose use in maintenance of exposed buildings and structures.

SURFACE PREPARATION:

All surfaces should be clean, dry and free from oil, grease, dust, dirt, loose paint or other foreign matter. Excess water should be removed, if possible, before application of 19 Ultra. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals.

APPLICATION:

Spread KARNAK 19 Ultra Flashing Cement to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks.

TO REPAIR CRACKS, BREAKS AND BLISTERS:

1. Spread KARNAK 19 Ultra Flashing Cement over the damaged area at an average thickness of 1/8".
2. Embed KARNAK Cotton, Glass or Polyester Membrane reinforcement in the 19 Ultra Flashing Cement.
3. Apply an additional coat of KARNAK 19 Ultra Flashing Cement over the entire patch at an average thickness of 1/8".

SPECIFICATIONS:

ASTM D-4586 Type I Class I & Class II

ASTM D-3409

Fed Spec SS-C-153 Type I (Asbestos-Free)

PHYSICAL PROPERTIES:

1. Consistency: A smooth rubber-like trowel consistency which will readily spread on and adhere to vertical and horizontal surfaces without sagging.
2. Character of Dried Film: Excellent adhesion to masonry, steel, cured concrete, shingles, asphalt roofing, skylight flashings and a variety of other surfaces.
3. Film Performance Characteristics: The dried film retains its elasticity and ductility so that the material will resist extreme variations in temperature and weather.
4. Sag Resistance: Excellent resistance to flow at high roof temperatures on vertical surfaces.
5. Homogenized: Thoroughly mixed and consistent throughout.
6. Consistency: 19 Ultra is always smooth and of a trowel consistency.

KARNAK

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>



19 Ultra Rubberized Flashing Cement (wet/dry)

CAUTION:

Combustible Mixture: do not use near open flame. Material is for building exterior applications only. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, **do not induce vomiting**. Call a physical immediately.

Keep out of reach of children. Keep container covered when not in use. **Do not thin**. Consult MSDS for further safety precautions. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

PACKAGING:

Available in 1 gallon cans, 3 gallon buckets, 5 gallon pails and 10.1 oz. cartridges.

If further information is needed, contact KARNAK Technical Services at 1-800-526-4236.

KARNAK

Revised 11.08.19

330 CENTRAL AVENUE, CLARK, NJ 07066
732-388-0300 • 800-526-4236 • FAX: 732-388-9422
WEB: <http://www.karnakcorp.com>

