

ROOFING

15 Smooth MUCK®



Read Safety Data Sheet before using this product.

DESCRIPTION: Smooth MUCK® asphalt flashing cement is composed of selected crude asphalts, fibers and refined solvents that dries to a tough waterproof coating. Use to seal leaks on asphalt roofs, concrete and metal roofs, shingles, gutters, downspouts, around chimneys, flues and skylights as well as for general purpose use in the maintenance of all exposed building and structures. Available in three consistencies: Summer, Semi and Winter Grade.

USES: Smooth MUCK is a general purpose flashing cement for repairing and sealing leaks on asphalt roofs, concrete and metal roofs, shingles, gutters, downspouts, around chimneys, flues and skylights as well as for general purpose use in the maintenance of all exposed building and structures.

FEATURES:

- Smooth trowel grade consistency
- Tough, waterproof film
- Won't run or sag on vertical surfaces

SURFACE PREPARATIONS: All surfaces should be dry, clean and free from oil or grease, dust, dirt, loose paint or other foreign matter. Recommended application temperature is 40°F to 120°F. If applying at temperatures lower than 40°F, the substrate must be free of moisture and/or ice crystals.

APPLICATION: Spread Smooth Muck to an average thickness of 1/8" (approximately 8 gallons per square) and press tightly into joints, seams or cracks. To repair large cracks, breaks and blisters, spread Smooth Muck over the damaged area then embed KARNAK 34 Asphalt Saturated Cotton, 31 Fiberglass Membrane or 5540 Resat-Mat Polyester membrane reinforcement and then apply another layer of Smooth Muck over the entire patch.

COVERAGE RATE: Apply each application at an average thickness of 1/8" (8 gallons per 100 sq. ft.)

CAUTION: Do not use near open flame. Avoid breathing solvent fumes and prolonged contact with skin. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Store in a heated room and keep container covered when not in use. Do not thin. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying. Exterior use only.

PACKAGING: Available in 5-gallon pails.

If further information is needed, contact KARNAK Technical services at 800-526-4236.

PHYSICAL PROPERTIES & SPECIFICATIONS

Weight per Gallon: 9.37 lbs.

Solids by Weight: 81% Nominal

Solids by Volume: 75% Nominal

Color: Black

Application Temp.: 40°F to 120°F

Service Temp
(Cured Film): 15°F to 180°F

VOC Content: 250 g/L MAX

ASTM D4586 Type I Class I

SS-C-153 Type I

