

FABRIC

31 Fiberglass Membrane



Read Safety Data Sheet before using this product.

DESCRIPTION: 31 Fiber Glass Membrane is a waterproofing fabric woven entirely of fiberglass yarn. It is ideal for use with cold application cements and coatings, and being of high flexibility, conforms to all contours and bends as required in general roofing and waterproofing maintenance.

USES: 31 Fiberglass Membrane is used to reinforce flashing cements and liquid applied mastics and coatings.

FEATURES, BENEFITS & ADVANTAGES:

- Contour flexibility without cracking
- High tensile strength
- Will not mildew, rot or decay
- Acid and alkali resistant

PACKAGING:

4" X 150'	18 rolls/carton
6" x 150'	12 rolls/carton
9" x 150'	12 rolls/carton
12" x 150'	6 rolls/carton
18" x 150'	6 rolls/carton
36" x 150'	6 roll/carton

COMPATIBILITY: 31 Fiber Glass Membrane is treated with a synthetic resin in the proper balance to give complete compatibility with asphalt or tar and all accepted waterproofing and coating compounds.

If further information is needed, contact KARNAK Technical services at 800-526-4236.

PHYSICAL PROPERTIES & SPECIFICATIONS

Weight:	2.0 oz. per yd ² nominal 6.5 lbs. per 36" x 150' roll
Thread Count:	20 x 10
Tear Strength (Warp):	75 lbs./lin. inch, nominal
(Fill):	75 lbs./lin. Inch, nominal
VOC Content:	0 g/L MAX

ASTM D1668 Type III

HH-C466b